

S5000 - L/F - CCF - CCP | Guía de selección / Selection guide

S5000 - L/F - CCF - CCP | 选型指南 / Selection guide



安培 Amps (Ith)	规格 Size	系列 Series	连接 Connection	开关 I - O - II Changeover switch I - O - II		直接手柄 Direct handle		外部手柄 External handle		
				3P	3P+N ^{(*)1}	蓝色 / Blue		蓝色 / Blue		
						型号 Code	型号 Code	型号 Code	型号 Code	L (mm)
40	00	S5L		S5L00403PB0	S5L00403NB0	D5LSI01	D5LLA01	177	85...180,5	
63	00	S5L		S5L00633PB0	S5L00633NB0	D5LSI01	D5LLA01	177	85...180,5	
80	00	S5L		S5L00803PB0	S5L00803NB0	D5LSI01	D5LLA01	177	85...180,5	
125	0	SSF		S5F01253P50	S5F01253N50	D5LSI01	D5LLA01	177	163...250,5	
125	0	S5L		S5L01253PB0	S5L01253NB0	D5LSI01	D5LLA01	177	87...198	
160	0	SSF		S5F01603P50	S5F01603N50	D5LSI01	D5LLA01	177	163...250,5	
160	0	S5L		S5L01603PB0	S5L01603NB0	D5LSI01	D5LLA01	177	87...198	
200	0	SSF		S5F02003P50	S5F02003N50	D5LSI01	D5LLA01	177	163...250,5	
200	1	CCF		CCF02003P50	CCF02003N50	DCCLI11	DCCLA11	227	166...293	
200	1	CCP		CCP02003P50	CCP02003N50	DCCLI11	DCCLA11	227	166...293	
250	1	CCF		CCF02503P50	CCF02503N50	DCCLI11	DCCLA11	227	166...293	
250	1	CCP		CCP02503P50	CCP02503N50	DCCLI11	DCCLA11	227	166...293	
315	1	CCF		CCF03153P50	CCF03153N50	DCCLI11	DCCLA11	227	166...293	
315	1	CCP		CCP03153P50	CCP03153N50	DCCLI11	DCCLA11	227	166...293	
400	1	CCF		CCF04003P50	CCF04003N50	DCCLI11	DCCLA11	227	166...293	
400	1	CCP		CCP04003P50	CCP04003N50	DCCLI11	DCCLA11	227	166...293	
500	2	CCF		CCF05003P50	CCF05003N50	DCCLI21	DCCLA21	195	195...272	
500	2	CCP		CCP05003P50	CCP05003N50	DCCLI21	DCCLA21	195	195...272	
630	2	CCF		CCF06303P50	CCF06303N50	DCCLI21	DCCLA21	195	195...272	
630	2	CCP		CCP06303P50	CCP06303N50	DCCLI21	DCCLA21	195	195...272	
800	2	CCF		CCF08003P50	CCF08003N50	DCCLI21	DCCLA21	195	195...272	
800	2	CCP		CCP08003P50	CCP08003N50	DCCLI21	DCCLA21	195	195...272	
1000	3	CCF		CCF10003P50	CCF10003N50	DCCLI31	DCCLA31	186	223...298	
1000	3	CCP		CCP10003P50	CCP10003N50	DCCLI31	DCCLA31	186	223...298	
1250	3	CCF		CCF12503P50	CCF12503N50	DCCLI31	DCCLA31	186	223...298	
1250	3	CCP		CCP12503P50	CCP12503N50	DCCLI31	DCCLA31	186	223...298	
1600	4	SSF		S5F16003P50	S5F16003N50	D5LLI32	D5LLA31	239	418...573	
1800	4	SSF		S5F18003P50	S5F18003N50	D5LLI32	D5LLA31	239	418...573	
2000	5	SSF		S5F20003P50	S5F20003N50	DS-EI61	D5LENS1	333	788...938	
2500	5	SSF		S5F25003P50	S5F25003N50	DS-EI61	D5LENS1	333	788...938	
3150	5	SSF		S5F31503P50	S5F31503N50	DS-EI61	D5LENS1	333	788...938	

^{(*)1} 预切换中性极 (预跳 - 闭滞)。
^{(*)2} 250 Vac时, Ie = 16 A (电阻负载) 4 A (电感负载)。
^{(*)3} 手柄上的按钮扳动到“OFF”位置, 即可锁定外部配电箱的手柄 (也可以按要求在“ON”位置上锁定), 手柄锁定后方可拆除按键。

^{(*)4} Advanced switched neutral (early make - late break). ^{(*)5} Ie = 16 A (resistive loads) / 4 A (inductive loads) at 250 Vac. ^{(*)6} For external panel, lock the handle by means of a key in position "OFF", the key can only be removed with the handle locked. ^{(*)7} To protect the fix contacts at the rear part of the switch.
Also available: 4P (simultaneous 4-pole switching for dc applications) & 3P+Nf (fixed neutral) versions; DIN rail mounting kit from 125 A, 160 A (DS-DN01 x 2) code; Terminal shrouds and motorized unit (see page 17).

另有: 4P (直流电器同步4极切换)型和3P+Nf (固定中性线)型; 125A-160ADIN滑轨安装型, 编号 (DS-DN01x2); 端子罩和驱动电机组 (参见第17页)。



S5L系列转换开关的连接线路
Changeover switches S5L series connection



S5F系列转换开关的连接线路
Changeover switches S5F series connection



CCF-CCP系列转换开关的连接线路
Changeover switches CCF-CCP series connection

• 尺寸, 参见第36 - 47页 / Dimensions, see page 36 - 47
 • 技术参数, 参见第60页 / Technical information, see page 60

辅助触点 Auxiliary contacts 1NO+1NC 2NO+2NC	桥式连接 Bridging links	轴外伸部 / Shaft extensions						保护背板 Rear protective plate - 4P	安全按键锁定装置 ^{(*)4} Safety key lock device ^{(*)5}	
		1类 / Type 1			2类 / Type 2				单 Simple	双 Double
		型号 Code	L (mm)	P (mm)	型号 Code	L (mm)	P (mm)		型号 Code	型号 Code
D5LAU01	D5LAU02	D5LPCB1	DS-EP04	250	85...253,5	DS-EP05	387	85...390,5	-	-
D5LAU01	D5LAU02	D5LPCB1	DS-EP04	250	85...253,5	DS-EP05	387	85...390,5	DS-CAB1	DS-CEB1
DS-AU11	DS-AU12	D5LPC03	DS-EP04	250	163...323,5	DS-EP05	387	163...460,5	-	-
D5LAU01	D5LAU02	D5LPC01	DS-EP04	250	87...271	DS-EP05	387	87...408	-	-
DS-AU11	DS-AU12	D5LPC03	DS-EP04	250	163...323,5	DS-EP05	387	163...460,5	DS-CAB1	DS-CEB1
D5LAU01	D5LAU02	D5LPC01	DS-EP04	250	87...271	DS-EP05	387	87...408	-	-
DS-AU11	DS-AU12	D5LPC03	DS-EP04	250	163...323,5	DS-EP05	387	163...460,5	-	-
D5LAU01	D5LAU02	-	DS-EP14	376	166...442	DS-EP15	536	166...602	DCCPP12	-
D5LAU01	D5LAU02	-	DS-EP14	376	166...442	DS-EP15	536	166...602	DCCPP12	-
D5LAU01	D5LAU02	-	DS-EP14	376	166...442	DS-EP15	536	166...602	DCCPP12	DS-CB11
D5LAU01	D5LAU02	-	DS-EP14	376	166...442	DS-EP15	536	166...602	DCCPP12	D5LFC11
D5LAU01	D5LAU02	-	DS-EP14	376	166...442	DS-EP15	536	166...602	DCCPP12	-
D5LAU01	D5LAU02	-	DS-EP14	376	166...442	DS-EP15	536	166...602	DCCPP12	-
D5LAU01	D5LAU02	-	DS-EP14	376	166...442	DS-EP15	536	166...602	DCCPP12	-
D5LAU01	D5LAU02	-	DS-EP32	336	195...413	DS-EP24	535	195...612	DCCPP22	-
D5LAU01	D5LAU02	-	DS-EP32	336	195...413	DS-EP24	535	195...612	DCCPP22	-
D5LAU01	D5LAU02	-	DS-EP32	336	195...413	DS-EP24	535	195...612	DCCPP22	D5LCB21
D5LAU01	D5LAU02	-	DS-EP32	336	195...413	DS-EP24	535	195...612	DCCPP22	D5LFC21
D5LAU01	D5LAU02	-	DS-EP32	336	195...413	DS-EP24	535	195...612	DCCPP22	-
D5LAU01	D5LAU02	-	DS-EP32	336	223...448	DS-EP24	535	223...645	DCCPP32	-
D5LAU01	D5LAU02	-	DS-EP32	336	223...448	DS-EP24	535	223...645	DCCPP32	D5LCB31
D5LAU01	D5LAU02	-	DS-EP32	336	223...448	DS-EP24	535	223...645	DCCPP32	D5LFC31
DS-AU11	DS-AU12	D5LPC42	待议 Consult	待议 Consult	待议 Consult	待议 Consult	待议 Consult	待议 Consult	-	-
DS-AU11	DS-AU12	D5LPC42	待议 Consult	待议 Consult	待议 Consult	待议 Consult	待议 Consult	待议 Consult	D5LCB41	D5LFC41
DS-AU11	DS-AU12	待议 Consult	待议 Consult	待议 Consult	待议 Consult	待议 Consult	待议 Consult	待议 Consult	-	-
DS-AU11	DS-AU12	待议 Consult	待议 Consult	待议 Consult	待议 Consult	待议 Consult	待议 Consult	待议 Consult	D5LCB41	D5LFC41
DS-AU11	DS-AU12	-	-	-	-	-	-	-	-	-

UM - C | 选型指南 / Motorized unit - Selection guide

系列 Serie	规格 Size	UM外壳的尺寸 UM housing size	UM - C 电动单元 / Motorized unit		
			120 Vac 型号 / Code	230 Vac 型号 / Code	277 Vac 型号 / Code
CCF	1 (200 - 250 A)	T1	UM-C1120Z	UM-C11230Z	UM-C11277Z
CCF	1 (315 - 400 A)	T1	UM-C15120Z	UM-C151230Z	UM-C151277Z
CCF	2 (500 - 630 A)	T2	UM-C21120Z	UM-C21230Z	UM-C21277Z
CCF	2 (800 A)	T2	UM-C25120Z	UM-C25230Z	UM-C25277Z
CCF	3	T3	UM-C31120Z	UM-C31230Z	UM-C31277Z
SSF	4	T3	UM-C35120Z	UM-C35230Z	UM-C35277Z

驱动电机组电流可以高达3150安培。可与我公司协商。可以反向安装。按需求供货。

Motorized unit also available up to 3150 Amps. Please consult us. There are references for inverted mounting positions. Supply under request.

端子罩 CCF/P - 选型指南 / CCF/P Terminal shrouds - Selection guide

安培 / Amps	3极输入开关 I 3 poles input switch I	3极输入开关 II 3 poles input switch II	4极输入开关 I & II 4 poles input switches I & II	3极共用输出 3 poles common output	4极共用输出 4 poles common output
	型号 / Code	型号 / Code	型号 / Code	型号 / Code	型号 / Code
200...400	DM2CU11	DM2CU11	DM2CU13	DCCCU11	DCCCU12
500...800	DM2CU22	DM2CU21	DM2CU23	DCCCU21	DCCCU22
1000...1250	DM2CU32	DM2CU31	DM2CU33	DCCCU31	DCCCU32

S5000 | 尺寸 / Dimensions (mm)

S5000 | 尺寸 / Dimensions (mm)

外部手柄和钻孔 / Panel handle and drilling

系列 Series	安培 Amps (Ith)	规格 Size	外部手柄和钻孔 / Panel handle and drilling	
			正视图 Front view	俯视图 Side view
S5L	40 63 80	00		
	125 160	0		

直接手柄 / Direct handle

俯视图 Top view	配电柜上为手柄和锁定装置开设的钻孔 Panel drilling for handle and keylock device		尺寸 (mm) Dimensions (mm)
	单 / simple	双 / double	